



Stage diameter [mm]	Thrust at 150 bar [ton]
187	41.2
165	32.1
145	24.7
126	18.7
107	13.5

\*For loads over 20000 kg, request ball with Ø 68

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 5/1015/ 213	187	165	145	126	107					1015	425	213	60	19.3	78
B DWR 5/1115/ 213	187	165	145	126	107					1115	445	230	60	20.7	81
B DWR 5/1215/ 213	187	165	145	126	107					1215	465	247	60	22.5	85
B DWR 5/1315/ 213	187	165	145	126	107					1315	485	264	60	24.4	89
B DWR 5/1415/ 213	187	165	145	126	107					1415	505	282	60	26.3	92
B DWR 5/1515/ 213	187	165	145	126	107					1515	525	301	60	28.1	96
B DWR 5/1715/ 213	187	165	145	126	107					1715	565	338	60	31.8	104
B DWR 5/2000/ 213	187	165	145	126	107					2000	625	394	60	37.1	114

#### ACCESSORIES

Cradle (page 10.02)		Brackets (page 13.01, 12.01)		Turn adapters (page 11.01)	
CUL#CH		SU#CD	SU#AC	RSN#90ACXBC0	