



Stage diameter [mm]	Thrust at 150 bar [ton]
187	41.2
165	32.1
145	24.7
126	18.7
107	13.5
088	9.1

\*For loads over 20000 kg, request ball with Ø 68

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 6/1220/ 213	187	165	145	126	107	88				1220	425	213	60	20.8	80
B DWR 6/1340/ 213	187	165	145	126	107	88				1340	445	230	60	22.3	84
B DWR 6/1460/ 213	187	165	145	126	107	88				1460	465	247	60	24.3	88
B DWR 6/1580/ 213	187	165	145	126	107	88				1580	485	264	60	26.3	92
B DWR 6/1700/ 213	187	165	145	126	107	88				1700	505	282	60	28.3	95
B DWR 6/1820/ 213	187	165	145	126	107	88				1820	525	301	60	30.3	100
B DWR 6/2060/ 213	187	165	145	126	107	88				2060	565	338	60	34.2	107
B DWR 6/2400/ 213	187	165	145	126	107	88				2400	625	394	60	39.8	118

#### ACCESSORIES

Cradle (page 10.02)		Brackets (page 13.01, 12.01)		Turn adapters (page 11.01)	
CUL#CH		SU#CD	SU#AC	RSN#90ACXBC0	