



| Stage diameter [mm] | Thrust at 150 bar [ton] |
|---------------------|-------------------------|
| 187 | 41.2 |
| 165 | 32.1 |
| 145 | 24.7 |
| 126 | 18.7 |
| 107 | 13.5 |
| 088 | 9.1 |
| 069 | 5.6 |

*For loads over 20000 kg, request ball with Ø 68

| Cylinder Description | Ø Stages [mm] | | | | | | | | | Stroke [mm] | E [mm] | R [mm] | Ø Ball [mm] | Capacity [Lt] | Weight [Kg] |
|----------------------|---------------|-----|-----|-----|-----|----|-----|------|----|-------------|--------|--------|-------------|---------------|-------------|
| | I | II | III | IV | V | VI | VII | VIII | IX | | | | | | |
| B DWR 7/1425/ 213 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | | 1425 | 425 | 213 | 60 | 21.7 | 83 |
| B DWR 7/1565/ 213 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | | 1565 | 445 | 230 | 60 | 23.3 | 90 |
| B DWR 7/1705/ 213 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | | 1705 | 465 | 247 | 60 | 25.3 | 92 |
| B DWR 7/1845/ 213 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | | 1845 | 485 | 264 | 60 | 27.4 | 95 |
| B DWR 7/1985/ 213 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | | 1985 | 505 | 282 | 60 | 29.5 | 100 |
| B DWR 7/2125/ 213 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | | 2125 | 525 | 301 | 60 | 31.6 | 104 |
| B DWR 7/2405/ 213 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | | 2405 | 565 | 338 | 60 | 35.7 | 112 |
| B DWR 7/2800/ 213 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | | 2800 | 625 | 394 | 60 | 41.5 | 124 |

ACCESSORIES

| | | | | | |
|---------------------|--|------------------------------|-------|----------------------------|--|
| Cradle (page 10.02) | | Brackets (page 13.01, 12.01) | | Turn adapters (page 11.01) | |
| CUL#CH | | SU#CD | SU#AC | RSN#90ACXBC0 | |