



\*For loads over 20000 kg, request ball with Ø 68

Stage diameter [mm]	Thrust at 150 bar [ton]
187	41.2
165	32.1
145	24.7
126	18.7
107	13.5
088	9.1
069	5.6

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 7/1425/ 213	187	165	145	126	107	88	69			1425	425	213	60	21.7	83
B DWR 7/1565/ 213	187	165	145	126	107	88	69			1565	445	230	60	23.3	90
B DWR 7/1705/ 213	187	165	145	126	107	88	69			1705	465	247	60	25.3	92
B DWR 7/1845/ 213	187	165	145	126	107	88	69			1845	485	264	60	27.4	95
B DWR 7/1985/ 213	187	165	145	126	107	88	69			1985	505	282	60	29.5	100
B DWR 7/2125/ 213	187	165	145	126	107	88	69			2125	525	301	60	31.6	104
B DWR 7/2405/ 213	187	165	145	126	107	88	69			2405	565	338	60	35.7	112
B DWR 7/2800/ 213	187	165	145	126	107	88	69			2800	625	394	60	41.5	124

#### ACCESSORIES

Cradle (page 10.02)		Brackets (page 13.01, 12.01)		Turn adapters (page 11.01)	
CUL#CH		SU#CD	SU#AC	RSN#90ACXBC0	