



Stage diameter [mm]	Thrust at 150 bar [ton]
187	41.2
165	32.1
145	24.7
126	18.7
108	13.8
092	9.9
076	6.8
060	4.2

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 8/1625/ 213	187	165	145	126	108	92	76	60		1625	435	222	60	21.7	
B DWR 8/1785/ 213	187	165	145	126	108	92	76	60		1785	455	239	60	23.9	
B DWR 8/1945/ 213	187	165	145	126	108	92	76	60		1945	475	256	60	26.0	
B DWR 8/2105/ 213	187	165	145	126	108	92	76	60		2105	495	273	60	28.2	96
B DWR 8/2265/ 213	187	165	145	126	108	92	76	60		2265	515	292	60	30.4	100
B DWR 8/2425/ 213	187	165	145	126	108	92	76	60		2425	535	310	60	32.6	106
B DWR 8/2745/ 213	187	165	145	126	108	92	76	60		2745	575	347	60	36.9	112
B DWR 8/3225/ 213	187	165	145	126	108	92	76	60		3225	635	404	60	43.4	126

#### ACCESSORIES

Cradle (page 10.02)		Brackets (page 13.01, 12.01)		Turn adapters (page 11.01)	
CUL#CH	SU#CD	SU#AC	RSN#90ACXBC0		