



Stage diameter [mm]	Thrust at 135 bar [ton]
210	46.7
187	37.1
165	28.9
145	22.2
126	16.8
107	12.1

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 6/1215/ 238	210	187	165	145	126	107				1215	435	230	68	26.9	106
B DWR 6/1335/ 238	210	187	165	145	126	107				1335	455	246	68	28.8	109
B DWR 6/1455/ 238	210	187	165	145	126	107				1455	475	263	68	31.4	113
B DWR 6/1575/ 238	210	187	165	145	126	107				1575	495	280	68	33.9	117
B DWR 6/1695/ 238	210	187	165	145	126	107				1695	515	298	68	36.5	122
B DWR 6/1815/ 238	210	187	165	145	126	107				1815	535	316	68	39.0	127
B DWR 6/2055/ 238	210	187	165	145	126	107				2055	575	353	68	44.3	138
B DWR 6/2400/ 238	210	187	165	145	126	107				2400	635	408	68	51.6	152

### ACCESSORIES

Cradle (page 10.04)		Brackets (page 12.01)		Turn adapters (page 11.01)	
CUL#CK			SU#AD	RSN#90ACXBC0	

BINOTTO S.R.L. IS COSTANTLY ENGAGED IN IMPROVING ITS PRODUCTS AND THEREFORE RESERVES THE RIGHT TO MODIFY WITHOUT ANY NOTICE, DATA, CHARACTERISTICS AND PERFORMANCES SHOWN.