



| Stage diameter [mm] | Thrust at 135 bar [ton] |
|---------------------|-------------------------|
| 210 | 46.7 |
| 187 | 37.1 |
| 165 | 28.9 |
| 145 | 22.2 |
| 126 | 16.8 |
| 107 | 12.1 |
| 088 | 8.2 |
| 069 | 5.0 |

| Cylinder Description | Ø Stages [mm] | | | | | | | | | Stroke [mm] | E [mm] | R [mm] | Ø Ball [mm] | Capacity [Lt] | Weight [Kg] |
|----------------------|---------------|-----|-----|-----|-----|-----|-----|------|----|-------------|--------|--------|-------------|---------------|-------------|
| | I | II | III | IV | V | VI | VII | VIII | IX | | | | | | |
| B DWR 8/1595/ 238 | 210 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | 1595 | 440 | 234 | 68 | 28.8 | 108 |
| B DWR 8/1755/ 238 | 210 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | 1755 | 460 | 250 | 68 | 30.8 | 113 |
| B DWR 8/1915/ 238 | 210 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | 1915 | 480 | 267 | 68 | 33.6 | 118 |
| B DWR 8/2075/ 238 | 210 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | 2075 | 500 | 285 | 68 | 36.4 | 123 |
| B DWR 8/2235/ 238 | 210 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | 2235 | 520 | 303 | 68 | 39.2 | 129 |
| B DWR 8/2395/ 238 | 210 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | 2395 | 540 | 321 | 68 | 42.0 | 134 |
| B DWR 8/2715/ 238 | 210 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | 2715 | 580 | 357 | 68 | 47.6 | 146 |
| B DWR 8/3170/ 238 | 210 | 187 | 165 | 145 | 126 | 107 | 88 | 69 | | 3170 | 640 | 413 | 68 | 56.0 | 160 |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

ACCESSORIES

| | | | | | | | | |
|---------------------|--|--|-----------------------|--|--|----------------------------|--|--|
| Cradle (page 10.04) | | | Brackets (page 12.01) | | | Turn adapters (page 11.01) | | |
| CUL#CK | | | SU#AD | | | RSN#90ACXBC0 | | |