



Stage diameter [mm]	Thrust at 135 bar [ton]
210	46.7
187	37.1
165	28.9
145	22.2
126	16.8
107	12.1
088	8.2
069	5.0

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 8/1595/ 238	210	187	165	145	126	107	88	69		1595	440	234	68	28.8	108
B DWR 8/1755/ 238	210	187	165	145	126	107	88	69		1755	460	250	68	30.8	113
B DWR 8/1915/ 238	210	187	165	145	126	107	88	69		1915	480	267	68	33.6	118
B DWR 8/2075/ 238	210	187	165	145	126	107	88	69		2075	500	285	68	36.4	123
B DWR 8/2235/ 238	210	187	165	145	126	107	88	69		2235	520	303	68	39.2	129
B DWR 8/2395/ 238	210	187	165	145	126	107	88	69		2395	540	321	68	42.0	134
B DWR 8/2715/ 238	210	187	165	145	126	107	88	69		2715	580	357	68	47.6	146
B DWR 8/3170/ 238	210	187	165	145	126	107	88	69		3170	640	413	68	56.0	160

ACCESSORIES

Cradle (page 10.04)			Brackets (page 12.01)			Turn adapters (page 11.01)		
CUL#CK			SU#AD			RSN#90ACXBC0		