



| Stage diameter [mm] | Thrust at 135 bar [ton] |
|---------------------|-------------------------|
| 210 | 46.7 |
| 187 | 37.1 |
| 165 | 28.9 |
| 145 | 22.2 |
| 126 | 16.8 |
| 108 | 12.4 |
| 092 | 8.9 |
| 076 | 6.1 |
| 060 | 4.1 |

| Cylinder Description | Ø Stages [mm] | | | | | | | | | Stroke [mm] | E [mm] | R [mm] | Ø Ball [mm] | Capacity [Lt] | Weight [Kg] |
|----------------------|---------------|-----|-----|-----|-----|-----|-----|------|----|-------------|--------|--------|-------------|---------------|-------------|
| | I | II | III | IV | V | VI | VII | VIII | IX | | | | | | |
| B DWR 9/1825/ 238 | 210 | 187 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | 1825 | 440 | 234 | 60 | 28.9 | 105 |
| B DWR 9/2005/ 238 | 210 | 187 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | 2005 | 460 | 250 | 60 | 31.8 | 112 |
| B DWR 9/2185/ 238 | 210 | 187 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | 2185 | 480 | 267 | 60 | 34.7 | 118 |
| B DWR 9/2365/ 238 | 210 | 187 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | 2365 | 500 | 285 | 60 | 37.6 | 121 |
| B DWR 9/2545/ 238 | 210 | 187 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | 2545 | 520 | 303 | 60 | 40.5 | 125 |
| B DWR 9/2725/ 238 | 210 | 187 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | 2725 | 540 | 321 | 60 | 43.4 | 134 |
| B DWR 9/3085/ 238 | 210 | 187 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | 3085 | 580 | 357 | 60 | 49.2 | 144 |
| B DWR 9/3625/ 238 | 210 | 187 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | 3625 | 640 | 413 | 60 | 57.9 | 166 |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

ACCESSORIES

| | | | | | | | | |
|---------------------|--|--|-----------------------|--|--|----------------------------|--|--|
| Cradle (page 10.04) | | | Brackets (page 12.01) | | | Turn adapters (page 11.01) | | |
| CUL#CK | | | SU#AD | | | RSN#90ACXBC0 | | |