



Stage diameter [mm]	Thrust at 135 bar [ton]
210	46.7
187	37.1
165	28.9
145	22.2
126	16.8
108	12.4
092	8.9
076	6.1
060	4.1

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 9/1825/ 238	210	187	165	145	126	108	92	76	60	1825	440	234	60	28.9	105
B DWR 9/2005/ 238	210	187	165	145	126	108	92	76	60	2005	460	250	60	31.8	112
B DWR 9/2185/ 238	210	187	165	145	126	108	92	76	60	2185	480	267	60	34.7	118
B DWR 9/2365/ 238	210	187	165	145	126	108	92	76	60	2365	500	285	60	37.6	121
B DWR 9/2545/ 238	210	187	165	145	126	108	92	76	60	2545	520	303	60	40.5	125
B DWR 9/2725/ 238	210	187	165	145	126	108	92	76	60	2725	540	321	60	43.4	134
B DWR 9/3085/ 238	210	187	165	145	126	108	92	76	60	3085	580	357	60	49.2	144
B DWR 9/3625/ 238	210	187	165	145	126	108	92	76	60	3625	640	413	60	57.9	166

ACCESSORIES

Cradle (page 10.04)		Brackets (page 12.01)		Turn adapters (page 11.01)	
CUL#CK			SU#AD	RSN#90ACXBC0	