



\* For loads over 30000 kg, request ball with Ø 80

Stage diameter [mm]	Thrust at 135 bar [ton]
236	59.0
210	46.7
187	37.1
165	28.9
145	22.2
126	16.8
107	12.1

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 7/1415/ 269	236	210	187	165	145	126	107			1415	445	248	68	36.3	136
B DWR 7/1555/ 269	236	210	187	165	145	126	107			1555	465	264	68	39.0	142
B DWR 7/1695/ 269	236	210	187	165	145	126	107			1695	485	280	68	42.5	147
B DWR 7/1835/ 269	236	210	187	165	145	126	107			1835	505	297	68	45.9	155
B DWR 7/1975/ 269	236	210	187	165	145	126	107			1975	525	315	68	49.4	161
B DWR 7/2115/ 269	236	210	187	165	145	126	107			2115	545	332	68	52.9	167
B DWR 7/2395/ 269	236	210	187	165	145	126	107			2395	585	368	68	59.9	178
B DWR 7/2800/ 269	236	210	187	165	145	126	107			2800	645	424	68	69.9	200

### ACCESSORIES

Cradle (page 10.05)		Brackets (page 12.01)		Turn adapters (page 11.01)	
CUL#CM		SU#AD		RSN#90ACXBC0	