



Stage diameter [mm]	Thrust at 135 bar [ton]
236	59.0
210	46.7
187	37.1
165	28.9
145	22.2
126	16.8
107	12.1
088	8.2

\* For loads over 30000 kg, request ball with Ø 80

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 8/1620/ 269	236	210	187	165	145	126	107	88		1620	445	248	68	37.8	135
B DWR 8/1780/ 269	236	210	187	165	145	126	107	88		1780	465	264	68	40.5	143
B DWR 8/1940/ 269	236	210	187	165	145	126	107	88		1940	485	280	68	44.1	148
B DWR 8/2100/ 269	236	210	187	165	145	126	107	88		2100	505	297	68	47.7	156
B DWR 8/2260/ 269	236	210	187	165	145	126	107	88		2260	525	315	68	51.4	163
B DWR 8/2420/ 269	236	210	187	165	145	126	107	88		2420	545	332	68	55.0	169
B DWR 8/2740/ 269	236	210	187	165	145	126	107	88		2740	585	368	68	62.2	184
B DWR 8/3200/ 269	236	210	187	165	145	126	107	88		3200	645	424	68	72.6	201

#### ACCESSORIES

Cradle (page 10.05)		Brackets (page 12.01)		Turn adapters (page 11.01)	
CUL#CM		SU#AD		RSN#90ACXBC0	