



Stage diameter [mm]	Thrust at 135 bar [ton]
236	59.0
210	46.7
187	37.1
165	28.9
145	22.2
126	16.8
107	12.1
088	8.2
069	5.0

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 9/1795/ 269	236	210	187	165	145	126	107	88	69	1795	450	252	68	38.1	138
B DWR 9/1975/ 269	236	210	187	165	145	126	107	88	69	1975	470	268	68	40.9	145
B DWR 9/2155/ 269	236	210	187	165	145	126	107	88	69	2155	490	285	68	44.6	151
B DWR 9/2335/ 269	236	210	187	165	145	126	107	88	69	2335	510	302	68	48.3	159
B DWR 9/2515/ 269	236	210	187	165	145	126	107	88	69	2515	530	319	68	52.0	168
B DWR 9/2695/ 269	236	210	187	165	145	126	107	88	69	2695	550	337	68	55.7	175
B DWR 8/3055/ 269	236	210	187	165	145	126	107	88	69	3055	590	373	68	63.2	188
B DWR 9/3570/ 269	236	210	187	165	145	126	107	88	69	3570	650	428	68	73.7	208

#### ACCESSORIES

Cradle (page 10.05)		Brackets (page 12.01)		Turn adapters (page 11.01)	
CUL#CM			SU#AD	RSN#90ACXBC0	