



Stage diameter [mm]	Thrust at 125 bar [ton]
265	68.9
236	54.7
210	43.3
187	34.3
165	26.7
145	20.6
126	15.6
107	11.2

\* For loads over 30000 kg, request ball with Ø 80

Cylinder Description	Ø Stages [mm]									Stroke [mm]	E [mm]	R [mm]	Ø Ball [mm]	Capacity [Lt]	Weight [Kg]
	I	II	III	IV	V	VI	VII	VIII	IX						
B DWR 8/1615/ 300	265	236	210	187	165	145	126	107		1615	455	266	68	47.7	171
B DWR 8/1775/ 300	265	236	210	187	165	145	126	107		1775	475	282	68	52.4	180
B DWR 8/1935/ 300	265	236	210	187	165	145	126	107		1935	495	298	68	57.0	186
B DWR 8/2095/ 300	265	236	210	187	165	145	126	107		2095	515	315	68	61.7	195
B DWR 8/2255/ 300	265	236	210	187	165	145	126	107		2255	535	332	68	66.3	202
B DWR 8/2415/ 300	265	236	210	187	165	145	126	107		2415	555	349	68	71.0	211
B DWR 8/2735/ 300	265	236	210	187	165	145	126	107		2735	595	384	68	80.3	228
B DWR 8/3200/ 300	265	236	210	187	165	145	126	107		3200	655	439	68	93.1	252

#### ACCESSORIES

Cradle (page 10.06)		Brackets (page 12.01)		Turn adapters (page 11.02, 11.03)	
CUL#CQ		SU#AE		RSN#90ADXBD0	RSN#00ADXAD1