



| Stage diameter [mm] | Thrust at 150 bar [ton] |
|---------------------|-------------------------|
| 145 | 24.7 |
| 126 | 18.7 |
| 108 | 13.7 |
| 092 | 9.9 |
| 076 | 6.8 |
| 060 | 4.2 |
| | |
| | |

| Cylinder Description | Ø Stages [mm] | | | | | | | | | Stroke [mm] | E [mm] | R [mm] | Ø Ball [mm] | Capacity [Lt] | Weight [Kg] |
|----------------------|---------------|-----|-----|----|----|----|-----|------|----|-------------|--------|--------|-------------|---------------|-------------|
| | I | II | III | IV | V | VI | VII | VIII | IX | | | | | | |
| B DWR 6/1230/ 168 | 145 | 126 | 108 | 92 | 76 | 60 | | | | 1230 | 420 | 196 | 60 | 12.6 | 50 |
| B DWR 6/1350/ 168 | 145 | 126 | 108 | 92 | 76 | 60 | | | | 1350 | 440 | 213 | 60 | 13.4 | 53 |
| B DWR 6/1470/ 168 | 145 | 126 | 108 | 92 | 76 | 60 | | | | 1470 | 460 | 231 | 60 | 14.6 | 56 |
| B DWR 6/1590/ 168 | 145 | 126 | 108 | 92 | 76 | 60 | | | | 1590 | 480 | 250 | 60 | 15.7 | 58 |
| B DWR 6/1710/ 168 | 145 | 126 | 108 | 92 | 76 | 60 | | | | 1710 | 500 | 268 | 60 | 16.3 | 61 |
| B DWR 6/1830/ 168 | 145 | 126 | 108 | 92 | 76 | 60 | | | | 1830 | 520 | 287 | 60 | 18.0 | 64 |
| B DWR 6/2070/ 168 | 145 | 126 | 108 | 92 | 76 | 60 | | | | 2070 | 560 | 324 | 60 | 20.3 | 69 |
| B DWR 6/2400/ 168 | 145 | 126 | 108 | 92 | 76 | 60 | | | | 2400 | 620 | 383 | 60 | 23.8 | 75 |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

ACCESSORIES

| | | | | | |
|---------------------|--|------------------------------|-------|----------------------------|--|
| Cradle (page 10.01) | | Brackets (page 13.01, 12.01) | | Turn adapters (page 11.01) | |
| CUL#C4 | | SU#CC | SU#AB | RSN#90ABXBC0 | |