



| Stage diameter [mm] | Thrust at 150 bar [ton] |
|---------------------|-------------------------|
| 165 | 32.1 |
| 145 | 24.7 |
| 126 | 18.7 |
| 108 | 13.8 |
| 092 | 9.9 |
| 076 | 6.8 |
| 060 | 4.2 |

| Cylinder Description | Ø Stages [mm] | | | | | | | | | Stroke [mm] | E [mm] | R [mm] | Ø Ball [mm] | Capacity [Lt] | Weight [Kg] |
|--------------------------|---------------|------------|------------|------------|-----------|-----------|-----------|------|----|-------------|------------|------------|-------------|---------------|-------------|
| | I | II | III | IV | V | VI | VII | VIII | IX | | | | | | |
| B DWR 7/1430/ 188 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | | | 1430 | 425 | 205 | 60 | 16.4 | 64 |
| B DWR 7/1570/ 188 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | | | 1570 | 445 | 222 | 60 | 17.6 | 68 |
| B DWR 7/1710/ 188 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | | | 1710 | 465 | 240 | 60 | 19.2 | 71 |
| B DWR 7/1850/ 188 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | | | 1850 | 485 | 258 | 60 | 20.8 | 74 |
| B DWR 7/1990/ 188 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | | | 1990 | 505 | 277 | 60 | 22.4 | 76 |
| B DWR 7/2130/ 188 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | | | 2130 | 525 | 295 | 60 | 23.9 | 80 |
| B DWR 7/2410/ 188 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | | | 2410 | 565 | 332 | 60 | 27.1 | 87 |
| B DWR 7/2800/ 188 | 165 | 145 | 126 | 108 | 92 | 76 | 60 | | | 2800 | 625 | 390 | 60 | 31.5 | 95 |

ACCESSORIES

| | | | | | |
|---------------------|--|------------------------------|-------|----------------------------|--|
| Cradle (page 10.02) | | Brackets (page 13.01, 12.01) | | Turn adapters (page 11.01) | |
| CUL#CH | | SU#CD | SU#AC | RSN#90ACXBC0 | |